

ARDEX installation recommendation for wall ceramics from Kaufmann Keramik GmbH



Kaufmann Keramik GmbH • Otto-Hahn-Straße 1 • 95111 Rehau • Tel: +49 (9283) 89806-0

Wall ceramics in wet interior areas

Jointing mortar	ARDEX G 10				
Tile adhesives	ARDEX X 77				
Waterproofing	ARDEX S 7 PLUS or ARDEX SK 100 W (glued with ARDEX S 7 PLUS, ARDEX 7 + 8) or ARDEX 8 + 9				
Compensation	ARDEX A 950				
Precoat	ARDEX P 51 Mixing ratio 1:3 with water		ARDEX P 51 Mixing ratio 1:1 with water		ARDEX P 4
Underground	Cement plaster	Masonry	Plasterboards	Concrete	old tiles

Preparation of the substrate

The substrate must meet the requirements of the applicable technical guidelines, standards and data sheets. In particular, it must be level, permanently dry, solid, load-bearing, free from separating agents and cracks, and resistant to tension and pressure, or must be prepared accordingly.

In the ARDEX system

The combination with other ARDEX products classified in EMICODE EC1 is an optimal prerequisite for very low emission and odourless structures. We guarantee the perfect quality of our products. Our processing recommendations are based on tests and practical experience. However, they can only be general instructions without any guarantee of properties, as we have no influence on the conditions on site and the execution of the work. When processing, the instructions and specifications in the technical data sheets of ARDEX GmbH must be observed. Country-specific regulations based on regional standards, building regulations, processing or industrial guidelines may lead to specific processing recommendations. Translated with www.DeepL.com/Translator (free version)